



SUIPA

Construction Chemicals

SUIPA ROAD LINE PAINT

Alkyd-Based Road Marking Paint

PRODUCT DESCRIPTION

It is a solvent-based road marking paint formulated with alkyd resin.

APPLICATIONS

It is utilized for delineating and marking urban and intercity roads, airports, parking facilities, warehouses, and various types of areas.

FEATURES

Due to its exceptional durability, it retains its reflective properties, color, and film thickness for prolonged durations even under intense traffic conditions. It provides superior UV and chemical resistance. Light reflection is facilitated by glass beads that are applied to surfaces and scattered on top. Depending on the pigment utilized, any desired hue can be attained.

SURFACE PREPARATION

Prior to application, verify that the surface is dry, devoid of dust, and free from oil and other contaminants. It is advisable to clean any existing paint.

APPLICATION

It is advisable to apply the product by spraying the road surface using automatic application equipment, followed by the sprinkling of glass beads on top. Alternatively, application may be performed with a brush or roller if required. As the product is ready for use, thinning is not necessary; however, if needed, it can be thinned with a suitable thinner. It is essential to wear gloves and a mask during the application process.

TECHNICAL SPECIFICATIONS

Color Drying Time	White
Application	20 min
Conditions	5 °C - 40 °C 80%
Maximum	90 ± 10 KU
Humidity Viscosity	1.60 g/ml ± 0.1 LF7/β
Density Gloss Level	≥ 0.85 UV 1
UV Resistance	At least 95%
Coverage Rate	6 months and over
Storage Stability	500-900 g/m ²
Wet Paint Usage	350 g/m ²
Glass Beads	

These values offer general information and are not included in the product specifications.

CONSUMPTION

500-900 g/m²

STORAGE

Store in original, sealed containers, in dry conditions, at temperatures ranging from 5 to 25°C. Avoid exposing packaging to direct sunlight. Keep away from sources of ignition. Under these conditions, the material's shelf life is one year.

AMBALAJ

20 kg Metal Tin